



Motor Oil & Lubricants

FELIX ULTRA F

10W/30 SM/CF

FELIX ULTRA F 10W/30, is four season engine oil which has been formulated with synthetic oils and performance additives for superior protection and excellent fluidity. It has been developed to be used in diesel engines Passenger and commercial vehicles engines which work by gasoline. It can be safely used in Cars, vans and small commercial vehicles engines.

Properties

- Provides fuel economy and long service life by excellent viscosity control property.
- It forms extra protection layer against to abrasion by bonding to surface of engines with smart molecules that contains.
- It makes easy to work at cold weather by its viscosity.
- Provides high resistance to tear due to high viscosity index.

Approvals and Specifications

- API SM / API SL
- ACEA A3/B3/B4
- Peugeot/Citroën Automobiles B71 2296
- MB-Approval 229.3
- Volkswagen VW50200
- Renault RN0700
- Opel GM-LL-A-025
- BMW Longlife-01
- API CF
- Porsche A40
- AVTOVAZ (LADA cars)
- MB-Approval 229.5
- Volkswagen VW50500
- Renault RN0710
- Opel GM-LL-B-025



Motor Oil & Lubricants

FELIX ULTRA F

10W/30 SM/CF

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,3 - 12,5
● Viscosity Index	ASTM D2270	Min. 140
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -33