GEARTECH

80W-90 GL-5

GEARTECH 80W-90 is a high-performance gear lubricant formulated from select base oils and an advanced additive system. It can be used for on-highway light- and heavy-duty trucks, buses, vans and cars. **GEARTECH 80W-90** provides increased protection and lubrication of the gearbox and the transaxle over a wide temperature range.

Properties

Motor Oil & Lubricants

- Increased protection against wear and tear, also under high stress working conditions.
- Have extreme pressure (EP) resistant to corrosion and oxidation and antifoaming properties.
- Prevents metal-to-metal contact by maintaining a sufficient oil film between the parts
- Have excellent antiwear, antifoam, anticorrosion and antirust properties

Approvals and Specifications

- API GL-5/GL-4
- MAN 342M-1, MAN 342 M-2
- Volvo 1273.12
- U.S. Steel 224

- ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B
- Scania STO 1:0
- DIN 51517 Part 3
- AGMA 9005-D94

Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	14,5 - 18,5
Viscosity Index	ASTM D2270	Min. 100
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max21