



Motor Oil & Lubricants

FELIX ULTRA

5W-40 SM/CF

FELIX ULTRA 5W-40 is full synthetic engine oil which perfectly adapted to all types of modern vehicles, passenger cars, SUVs and off-road cars equipped with catalysts and using unleaded fuel or liquefied petroleum gas (LPG). It is particularly suited to turbocharged, multi-valve and direct injection engines. It's not recommended for Diesel particulate filters (DPF) and gasoline catalytic converters (CAT's) vehicles.

Properties

- Shows excellent thermal and oxidation stability.
- Contains intelligent molecules that cling to your engine and form an extra layer that protects from start up.
- Provides high resistance to tear due to high viscosity index.
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives.
- Provides superior performance under extreme cold start up conditions.

Approvals and Specifications

- API SM / API SL
- ACEA A3/B3/B4
- MB-Approval 229.3
- Renault RN0700
- Volkswagen VW50200
- Porsche A40
- Opel GM-LL-A-025
- AVTOVAZ (LADA cars)
- API CF
- Peugeot/Citroën Automobiles B71 2296
- MB-Approval 229.5
- Renault RN0710
- Volkswagen VW50500
- BMW Longlife-1
- Opel GM-LL-B-025



Motor Oil & Lubricants

Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 – 16,3
Viscosity Index	ASTM D2270	Min. 155
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -35
Total Base Number, mg KOH/g	ASTM D2896	Min. 7,0

