

FELIX ULTRA FULLY

SYNTHETIC HYBRID 0W-16 SN PLUS

FELIX ULTRA FULLY SYNTHETIC HYBRID 0W-16 is a low viscosity, advanced fully synthetic engine oil designed to help provide exceptional engine protection and enhanced fuel economy to keep your engine running like new and protect critical engine parts up to 16,000 kilometers between oil changes.

Properties

- Its excellent fluidity in cold weather conditions provides rapid lubrication of engine parts during startup, thus protecting the engine against wear.
- Superior thermal and oxidation stability maintains performance during the extended oil drain interval recommended by engine manufacturers.
- Enhanced frictional properties provide extreme fuel economy.

Approvals and Specifications

- API SN PLUS / API SN / API SM
- ILSAC GF-5 / GF-4 / GF-3
- ACEA C2-12 / C2-16
- ACEA C3-12 / C3-16
- ACEA C5-16
- Dexos 1
- MB-Approval 229.52
- Volkswagen VW50400 / VW50700
- Ford WSS-M2C947-B1
- Ford WSS-M2C947-A



Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	6,1 – 8,2
Viscosity Index	ASTM D2270	Min. 160
Flash Point, °C	ASTM D92	Min. 195
Pour Point, °C	ASTM D97	Max39
Total Base Number, mg KOH/g	ASTM D2896	Min. 8,5